

SAFETY DATA SHEET

according to 1907/2006/EC

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

JohnsonDiversey

JohnsonDiversey UK Limited

Weston Favell Centre Northampton NN3 8PD Tel 01604 405311 Fax 01604 406809 Emergency Call 0800 052 0185

E-Mail: MSDSinfoUK@johnsondiversey.com

Clearance Code
R57408

TASKI TAPI GUM C4q
Professional cleaning/maintenance product for building care

Product Code
MSDS4747

TO :

2. HAZARDS IDENTIFICATION

Extremely flammable.

This product contains a material with an WEL published in HSE document EH40.

3. COMPOSITION / INFORMATION ON INGREDIENTS.

CAS No	EINECS No			
		Active substance with propellant.		
106-97-8	203-448-7	Butane (WEL)	F: R13	(>30%)
74-98-6	200-827-9	Propane liquefied	F+: R12	(15-30%)

Ingredients according to EC 648/2004:

More than 30% : Aliphatic hydrocarbons

Full text of risk phrases are given in section 16.

4. FIRST AID MEASURES

- Eyes :** Rinse immediately with plenty of water, holding the eyelids open and seek medical advice if effects persist.
- Inhalation :** Remove from source of exposure. Obtain medical attention if symptoms develop.
- Skin :** Wash thoroughly.
- Ingestion :** Remove product from mouth, give the casualty a small quantity of water to drink and seek medical advice. Do not induce vomiting.

5. FIRE FIGHTING MEASURES

FLAMMABLE AEROSOL - In the event of a fire there is a severe risk of explosion and flash, aerosols stored in quantities likely to present a hazard should be cooled with water or water spray if this can be done without risk to firefighting personnel. May evolve toxic fumes if involved in a fire. Firefighters should wear self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Wear suitable protective clothing including gloves and eye/face protection. Accidental release would not normally occur with aerosols, however if a can or cans were leaking then ensure good ventilation and that all sources of ignition are removed.

7. HANDLING & STORAGE

Avoid contact with skin and eyes. Always ensure good ventilation when using this product. Protect against electrostatic charges. Do not mix with any other chemicals other than as advised by your JohnsonDiversey representative.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of reach of children.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

- Hand :** Personal protection is not normally required unless a risk assessment indicates the need for it.
- Eyes :** Personal protection is not normally required unless a risk assessment indicates the need for it.
- Skin :** Personal protection is not normally required unless a risk assessment indicates the need for it.
- Respiration :** Personal protection is not normally required unless a risk assessment indicates the need for it.

WEL : Butane (as propellant)
W.E.L. 1810 mg/cu.m 15 min ref time
W.E.L. 1450 mg/cu.m 8 hour TWA.

Propane liquefied
W.E.L. Asphyxiant

ref. HSE publication EH40

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance : Colourless aerosol

Odour : Characteristic

Solubility : Not miscible or difficult to mix with water.

10. STABILITY & REACTIVITY

Provided the product is stored in accordance with the approved guidelines there are no known hazardous decomposition products.

11. TOXICOLOGICAL INFORMATION

Eyes : Direct contact can damage the eye by freezing.

Skin : Direct contact can damage skin by freezing

Inhalation : Capable of causing irritation. May cause asphyxia if very high concentrations inhaled.

Ingestion : Unlikely to be irritant in normal use.

12. ECOLOGICAL INFORMATION

When used for its intended purpose this product should not cause adverse effects in the environment.

13. DISPOSAL CONSIDERATIONS

The undiluted product is classified as hazardous waste with respect to The Hazardous Waste Regulations (2005) and The List of Wastes Regulations (2005). For the disposal of large quantities, contact your licensed waste contractor.

European waste catalogue 16 05 04 Gases in containers (including halons) containing dangerous substances.

If possible, rinse out the container thoroughly after use and dispose of appropriately as commercial waste, or alternatively dispose of the contaminated container via a licensed waste contractor. Observe all local and regional waste regulations.

14. TRANSPORT INFORMATION

EEC Regulation : AEROSOLS, UN1950, Class 2.1

IMDG/UN : Aerosols, UN1950, Class 2.1

RID/ADR : Aerosols, UN1950, Class 2.1

ICAO/IATA : Passenger Aircraft: 203, Y203
Cargo Aircraft: 203

15. REGULATORY INFORMATION

Hazard symbol : F+, EXTREMELY FLAMMABLE

Risk phrases : R12 Extremely flammable.

Safety phrases : S9 Keep container in a well-ventilated place.
S23 Do not breathe spray.
S51 Use only in well-ventilated areas.

16. OTHER INFORMATION

Handle and apply only as recommended, for full information see product information sheet.

Internal Reference:- MSDS4747-02 (31-Aug-2005), BC.CA.Cs04 (24-Feb-1998)

Text of risk phrases associated with ingredients listed in section 3.

R12 Extremely flammable
R13 Extremely flammable liquified gas
Change made to sections 2 and 13.